



EOS Organic W

Sauna heater for domestic sauna cabins. Wall-mounting model.

High-quality sauna heater for the Finnisch (dry) sauna. EOS Organic W impresses with its unique futuristic design. With the asymmetrical cut-outs in the top cover for air circulation and the curved edges, it is an absolute highlight in every sauna cabin.

Your advantages:

- Wall-mounting heater with curved edges and innovative design for dry Finnish sauna.
- Optimal relation between stone volume and air convection system for fast heat-up times and powerful water infusions.
- The asymmetrical cut-outs in the top cover not only ensure optimal air convection, but also give the sauna heater its unique design.
- The combination of brushed stainless steel and anthracite pearl effect finish on the outer shell underlines the modern character.
- Made in Germany quality from EOS.

Specifications:

Front side:	Zinc-plated steel, with anthracite pearl effect powder-coating
Top cover:	Brushed stainless steel
Inner shell / Rock store:	Stainless steel
Rear wall:	Stainless steel
Terminal box:	Stainless steel
Power range:	6.0, 7.5, 9.0, 10.0 and 10.5 kW
Power supply:	400 V 3N ~ 50 Hz
Rock store volume:	approx. 20 kg (Stones optionally available)
Dimensions (H x W x D):	650 x 410 x 385 mm (incl. wall bracket)
Installation:	Wall-mounted heater



Heater guard rail optionally available.




The laser-cut-outs in the top cover, the combination of modern brushed stainless steel and the elegant front in anthracite give this sauna heater its special futuristic look.




Connection diagram


6,0-10,0 kW



10,5 kW



Installation example




Technical specifications

Power output	Electrical connection	Connection mains - control unit	Connection control unit - heater	Connection mains - LSG	Connection LSG - heater	Connection control unit - LSG unit
6,0 kW	400 V 3N ~ 50 Hz	5 x 2,5 mm ²	5 x 1,5 mm ²	--	--	--
7,5 kW				--	--	--
9,0 kW				--	--	--
10,0 kW				--	--	--
10,5 kW				5 x 2,5 mm ²	5 x 1,5 mm ²	4 x 1,5 mm ²

All cross sections of a line are minimum diameters in mm² (copper wire).

Item no.	Power output	Electrical connection	Fuse protection (control unit)	Dimensions H/W/D, in cm	For sauna cabin size	Min. size air inlet and outlet	Weight without rocks	Power extension required
94 7549	6,0 kW	400 V 3N ~ 50 Hz	3 x 16 A	65 / 41 / 38,5	6 - 8 m ³	35 x 4 cm	22 kg	no
94 7550	7,5 kW				7 - 10 m ³	35 x 5 cm	22,5 kg	
94 7551	9,0 kW				9 - 14 m ³	35 x 6 cm	23 kg	
94 7890	10,0 kW				11 - 15 m ³	35 x 6 cm	23 kg	
94 7552	10,5 kW				23,5 kg	LSG 10		

Minimum clearances



Spare heating elements

Description	Item no.
For 6,0 kW (4x1500 W)	2000 8085
For 7,5 kW (5x1500 W)	2000 8085
For 9,0 kW (6x1500 W)	2000 8085
For 10,0 kW (6x1666 W)	2001 7026
For 10,5 kW (3x1500 W / 3x 2000W)	2000 8085 / 2000 8086

Suitable sauna control units

Model
EOS Econ D series (D1 up to 9,0 kW)
EOS Compact D series
EOS EmoTec D series
EOS EmoStyle D / Hi series
EOS EmoTouch 3 series